

P2.5

INDUSTRIAL SERIES INDOOR LED MODULE

SPECIFICATION



LED Lamp Specification

Lamp Brand	Color	Intensity	Wavelength	Testing Conditions
Nationstar	Red	450mcd	622nm	25°C,15mA
	Green	680mcd	530nm	25°C,8mA
	Blue	100mcd	472nm	25°C,5mA

Module Image



Module Specification

NO.	ITEMS	PARAMETER
1	Pixel Pitch Category	P2.5
2	Pixel pitch	2.5 mm
3	Pixel configuration	SMD Triad LED
4	Module dimension (W × H × D)	320 mm × 160 mm × 16.6 mm
5	Pixel density	160000 dots/m ²
6	Module resolution	128 × 64
7	Lamp Bead Dimensions	2121
8	Signal Source Interface	HUB75E
9	Brightness	1000 nits
10	Brightness Uniformity	≥ 97%
11	Color Temperature	3000 K to 10000 K adjustable
12	Color Uniformity	≤ ± 0.003Cx, Cy
13	Contrast Ratio	3000:1
14	Viewing Angle	160° (H)/160° (V)
15	Refresh Rate	≥4200 Hz
16	Scanning Amount	16
17	Grey Level	Up to 16 bit
18	Max. Consumption	≤ 420 W/m ²
19	Average Consumption	< 180 W/m ²
20	Input Voltage	DC: 4.5 V to 5 V
21	Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
22	Working Humidity	10% RH to 80% RH (without condensation)
23	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
24	Storage Humidity	10% RH to 85% RH (without condensation)
25	Package Dimensions (W × H × D)	673 (W) mm × 453 (H) mm × 390 (D) mm
26	Net Weight	16 kg (40 pcs in 1 box)



Metta Star Innovations

📞 98943 73741

✉️ contact@mettastar.in

🌐 www.mettastar.in

Registered Office: No:1439, 7th A Main Rd, Hampi Nagar, RPC Layout, Vijayanagar, Bengaluru, Karnataka-560104